DHI-HY-C152

Fire Alarm Bell

- Convenient installation, loud alarm sound
- Made of aluminum, light weight
- CE certified

System Overview

DHI-HY-C152 Fire Alarm Bell is the accessory for fire alarm system and security system. While confirming the fire, the alarm panel can be switched to announce the fire situation with high sound level and low current consumption.

Functions

Easy connection
After connecting the power cord, the device starts to ring.

Loud alarm sound
Over 95 dB(A) at 3 meters.

Scene

It is suitable for apartments, hotels, teaching buildings, office buildings, banks, libraries, warehouses, computer rooms, communication machine rooms, archives, and other industrial and civil buildings.

Technical Specification

Working Voltage	DC 24V
Current	30mA-45mA
Operating Temperature	–10°C to +55°C (+14°F to +131°F)
Operating Humidity	≤ 95% RH (no condensation)
Dimensions	ϕ150 mm × 50 mm (ϕ5.91" × 1.97")
Color	Red
Alarm Volume	Over 95dB (A) at 3 m (9.84 ft)
Installation	Wall Mount
Certification	CE

Installation

Dimensions (mm/inch)

Ordering Information

Type	Model	Description
Fire Alarm Bell	DHI-HY-C152	Fire Alarm Bell